fiberstruct
» grp gratings

Priemyselná 720
072 22 Strážske
Slovak Republic

tel.: +421/566871311
fax.: +421/566871399
info@fiberststruct.com


GRP Grating accessories

Adjustable Pedestals from 28 to 965mm



Adjustable
Support (Screwjack Pedestal)
From 28 to 965 mm

Slope corrector (BC-PH-5)
0 to 5% - 0 to 5 cm / m






Material:
Copolymer Polypropylene CPP
Thickness 3 to to 4.5 mm

Composition: 80% recycled PPC. 20% talc +UV black masterbatch and 100% recyclable

TECHNICAL FLOORS for Petro-chemical industry, photo laboratories, offshore oil industry, brewing industry, mecanical industry, etc.

Resisting UV light , weather , sea salt and almost all chemicals

Temerature range: -30°C to +90°C




fiberstruct
» grp gratings

Priemyselná 720
072 22 Strážske
Slovak Republic

tel.: +421/566871311
fax.: +421/566871399
info@fiberststruct.com

GRP Grating accessories

Type **PB -5** description



Height description	
PB-01	28 to 42 mm
PB-1	42 to 60 mm
PB-2	60 to 90 mm
PB-3	90 to 145 mm
PB- 4	145 to 245 mm
PB-5-NSC	230 to 315 mm
PB-6-NSC	285 to 367 mm
PB-7-NSC	365 to 485 mm
PB-8-NSC	452 to 605 mm
PB-9-NSC	537 to 725 mm
PB-10-NSC	620 to 845 mm
PB-11-NSC	705 to 965 mm

Security



PB Supporting Top head

Robust



COUPLER C1 = To Extend Screwjack Height

Stability



BOTTOM = Supporting Base